

DECLARATION OF PERFORMANCE (DoP)							
No. JL2016060ED							
16							

1.	Unique identification code of the product type	CLASSIC & FUNCTION EXTERNAL DOORS/ED
2.	Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4)	Annex1. Product Naming Statement Non-glazed single leaf door, <20% glazed single leaf door, >20% glazed single leaf door, Non- glazed double leaf door, <20% glazed double leaf door, >20% glazed double leaf door
3.	Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification as foreseen by the manufacturer	External door for domestic locations
4.	Name, registered trade name or registered trademark and contact address of the manufacturer as required under Article 11 (5)	JELD-WEN Latvija SIA, Rupniecibas iela 13 Aizkraukle LV-5101, Latvia www.jeld-wen.biz
5.	Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2)	N/A
6.	System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:	System 3
7.	In case of the declaration of performance concerning a construction product covered by a harmonized standard	Notified testing laboratory, SP Technical Research Institute of Sweden No. 0402, VTT Expert Services Oy No. 0809, TUV Eesti OU No. 1526 and DELTA Danish Electronics, Light and Acoustics No. 0199 performed the determination of the product-type on the basis of type testing (based on sampling carried out by the manufacturer), type calculation, tabulated values or descriptive documentation of the product under system 3 and issued test-/calculation reports.



	Non-glazed single leaf door	<20% glazed single leaf door	>20% glazed single leaf door	Non-glazed double leaf door	<20% glazed double leaf door	>20% glazed double leaf door	Harmonised technical specification	
Watertightness (Outswing)	7B	7B	7B	npd	npd	npd	EN 14351-	
Watertightness, (Inswing)	npd	npd	npd	npd	npd	npd		
Dangerous substances		· · ·	· · ·		· · · ·			
Resistance to wind load, (Outswing)	C3	C3	СЗ	npd	npd	npd		
Resistance to wind load, (Inswing)	C3	СЗ	СЗ	npd	npd	npd		
Impact resistance	n/a	npd	npd	n/a	npd	npd		
Load-bearing capacity of safety devices	n/a	n/a	n/a	n/a	n/a	n/a	1:2006 +A1:2010	
Height	npd	npd	npd	npd	npd	npd		
Acoustic performance	29(-3,-5) dB	29(-3,-5) dB	35(-2;-4) dB	npd	npd	npd		
Thermal transmittance	0,91	1,3	1,7	0,96 <sup>1</sup> 1,0 <sup>2</sup>	0,98 <sup>1</sup> 1,1 <sup>2</sup>	1,3 <sup>1</sup> 1,4 <sup>2</sup>		
Radiation properties g:	n/a	n/a	n/a	n/a	n/a	n/a		
Radiation properties LT:	n/a	n/a	n/a	n/a	n/a	n/a		
Air permeability, (Outswing)	4	4	4	npd	npd	npd		
Air permeability, (Inswing)	npd	npď	npd	npd	npd	npd		

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer

identified in point 4.

Signed for and on behalf of the manufacturer by:

Torben Porsholdt, CEO, JELD-WEN Northern Europe (Name and function)

(Place and date of issue) . . . .

/.... (Signature)